

## SJ6826/32 RT ROUGH TERRAIN SCISSORS

| Dimensions   | SJ6826 RT            | SJ6832 RT            |
|--|----------------------|----------------------|
| A Work Height  | 32' (9.75 m)         | 38' (11.58 m)        |
| B Raised Platform Height                                 | 26' (7.92 m)         | 32' (9.75 m)         |
| C Lowered Platform Height                                | 48.5" (1.23 m)       | 54" (1.37 m)         |
| D Overall Width  | 69.5" (1.76 m)       | 69.5" (1.76 m)       |
| E Overall Length   | 107" (2.72 m)        | 107" (2.72 m)        |
| F Stowed Height (Rails Up)                               | 93.5" (2.38 m)       | 99" (2.51 m)         |
| G Stowed Height (Rails Down)                             | 63.5" (1.61 m)       | 69" (1.75 m)         |
| H Platform Width (Inside Dimension)                      | 56" (1.42 m)         | 56" (1.42 m)         |
| l Platform Length (Inside Dimension)                     | 96" (2.44 m)         | 96" (2.44 m)         |
| Specifications   | SJ6826 RT            | SJ6832 RT            |
| Extension Deck   | 5' (1.52 m)          | 5' (1.52 m)          |
| Ground Clearance   | 8" (0.20 m)          | 8" (0.20 m)          |
| Wheelbase  | 80.5" (2.04 m)       | 80.5" (2.04 m)       |
| Weight   | 6,460 lbs (2,930 kg) | 7,590 lbs (3,443 kg) |
| Gradeability   | 45%                  | 40%                  |
| Turning Radius (Inside)                                  | 60" (1.52 m)         | 60" (1.52 m)         |
| Turning Radius (Outside)                                 | 156" (3.96 m)        | 156" (3.96 m)        |
| Lift Time (With Rated Load)                              | 36 sec               | 39 sec               |
| Lower time (With Rated Load)                             | 36 sec               | 36 sec               |
| Drive Speed (Stowed)                                     | 3.8 mph (6.1 km/h)   | 3.8 mph (6.1 km/h)   |
| Drive Speed (Raised)                                     | 0.4 mph (0.6 km/h)   | 0.4 mph (0.6 km/h)   |
| Maximum Drive Height                                     | Full Height          | Full Height          |
| Capacity (Overall)                                       | 1,250 lbs (567 kg)   | 1,000 lbs (454 kg)   |
| Distributed Capacity (Main Platform)                     | 950 lbs (431 kg)     | 700 lbs (318 kg)     |
| Distributed Capacity (Extension Deck)                    | 300 lbs (136 kg)     | 300 lbs (136 kg)     |
| Local Floor Load (With Rated Load)                       | 190 psi (1,310 kPa)  | 216 psi (1,500 kPa)  |
| Overall Floor Load (With Rated Load)                     | 170 psf (830 kg/m²)  | 200 psf (976 kg/m²)  |
| Maximum # of persons up to 28 mph (12.5 m/s) wind rating | 4                    | 4                    |
| Diesel Engine  | 24.8 HP Kubota       | 24.8 HP Kubota       |
| Fuel Tank  | 23 gal (87 L)        | 23 gal (87 L)        |
| Hydraulic Reservoir                                      | 23 gal (87 L)        | 23 gal (87 L)        |
| Outrigger Leveling (Front to Back / Side to Side)        | 5° / 8°              | 5° / 8°              |
| Tire Type  | Foam-Filled          | Foam-Filled          |
| Tire Size  | 26 x 12              | 26 x 12              |





## Skyjack Head Office

55 Campbell Rd. Guelph, ON Canada N1H 1B9 Sales Inquiries: 1-877-755-4387 (1-877-SJLIFTS) Main Switchboard: 1-800-265-2738

Main Switchboard: 1-800-265-27 Phone: 519-837-0888

Fax: 519-837-8104 Email: skyjack@skyjack.com



